

## AURA S3

Product Reference      Aura  
 EN ISO 20345:2011    S3 SRC ESD  
 Sizes                      36-47  
 Weight (s. 41)         570 gr.



**Model description:** Leather shoe, water repellent, black, mesh Nylon lining, antistatic, puncture resistant SJ Flex sole, shock proof, anti slip, composite toe, S3 Pu/Pu sole, ESD.

**Application areas:** Construction, Industry.

**Precaution and maintenance of the shoe:** To extend life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, neither nearby a heat source.

		Description	Measure Unit	Result	EN345 required
Complete shoe	Protection of toes: composite tip resistant to: A shock of 200 J Pressure of 1500 kg Sole: SJ FLEX resistant to 1100N	Impact resistance (Clearance after shock)	Mm	15,5	>14
		Compressive strength (after clearance compression)	Mm	18,5	14
	Anti-shock system: Low-Density polyurethane and profile of the heel	Shock absorption in heel	J	>35	>20
Upper	Black leather, water repellent, Thickness 1,6mm	Permeability to water vapor	Mg/m2 hour	>2,0	>0,8
		Permeability coefficient	Mg/cm2	>25,6	>20
		Water repellent	Minute	>90	<60
Front	Thickness 1,2mm	Permeability coefficient	Mg/cm2	>35	>30
Lining	Nylon mesh grey	Permeability to water vapor	Mg/cm2 hour	>2,1	>2
Back	Thickness 1,0mm	Permeability coefficient	Mg/cm2	>45	>30
Insole	Antistatic, absorbent, resistant to abrasion and to exfoliation	Abrasion resistance	Cycles	>400	>400
Outsole	Antistatic double density polyurethane injected directly onto the upper	Abrasion resistance (volume loss)	Mm3	110	<150
	Shock absorption, anti-slip, abrasion resistant, mineral oils and weak acids	Oil resistance (volume variation AV)	%	+1,0	<+12
		Coefficient of adhesion of the outsole	-	0,18	>0,15

*Our shoes are constantly evolving, the technical data above may change.*

*All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.*