



Dragon S3

Weight (s. 41)

Product Reference Dragon
Euronorm EN345 S3 SRC ESD
Sizes 38-47

Model description: metal free safety shoe in leather and nylon, black, breathable technomesh, ESD, shock proof, slip resistant, Nano carbon toe, S₃, PHYLON/RUBBER sole.

499 gr.



Application areas: industry, logistics, medical personnel, safety staff

Precaution and maintenance of the shoe: To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

		Description	Measure Unit	Result	EN345 required
Complete shoe	Protection of toes: nano carbon toe capp resistant to: A shock of 200 J Pressure of 1500 kg Midsole: puncture resitant lightweight , resistant to 100N	Impact resistance (Clearance after shock) Compressive strength (after clearance compression)	Mm Mm	14.5 16.5	>14
	Anti-shock system: low-Density polyurethane and profile of the heel	Shock absorption in heel	J	26	>20
Upper	Leather and nylon	Permeability to water vaper	Mg/m2 hour	3	>0,8
		Permeability coefficient	Mg/cm2	29	15
Lining	Technomesh	Permeability to water vapor	Mg/cm2 hour	3	>2
Outsole	Impact Phylon + natural rubber	Abrasion resistance (volume loss)	Mm ₃	123	<150
	Black, antistatic, anti-slip, abrasion resistant, mineral oils and weak acids	Oil resistance (volume variation AV)	%	10	<+12