

## Ligero S1P

Product Reference Ligero  
Euronorm EN345 S1P SRC ESD  
Sizes 36-47  
Weight (s. 41) 415 gr.



**Model description:** Mesh shoe, black /navy/navy-orange colour, breathable technomesh, ESD, shock proof, slip resistant, Nano carbon toe, S1P, PHYLON/RUBBER sole.

**Application areas:** industry, logistics, medical personnel.

**Precaution and maintenance of the shoe:** To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

		Description	Measure Unit	Result	EN345 required
Complete shoe	Protection of toes: nano carbon toe capp resistant to: A shock of 200 J Pressure of 1500 kg Midsole: puncture resistant lightweight, resistant to 100N	Impact resistance (Clearance after shock)	Mm	16	>14
		Compressive strength (after clearance compression)	Mm	18	14
	Anti-shock system: low-Density polyurethane and profile of the heel	Shock absorption in heel	J	24	>20
Upper	Breathable technomesh	Permeability to water vapor	Mg/m2 hour	35	>0,8
		Permeability coefficient	Mg/cm2	284	15
Lining	Technomesh	Permeability to water vapor	Mg/cm2 hour	73	>2
Outsole	Impact Phylon + natural rubber	Abrasion resistance (volume loss)	Mm3	65	<150
	Black, antistatic, anti-slip, abrasion resistant, mineral oils and weak acids	Oil resistance (volume variation AV)	%	8	<+12

Our shoes are constantly evolving, the technical data above may change.

All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.