

Pluto-EH S3

Product Reference Pluto
 En ISO20345:2011 S3 SRC
 Sizes 7-5-13
 Weight (s. 8) 1.366lb.



Model description: Leather shoe, water repellent, brown, Nylon mesh lining, puncture resistant SJ Flex sole, shock proof, slip resistant, composite toe, S3 PU/TPU sole.

Application areas: Construction, Manufacturing, Electric power station, Electric technician, Application connect to high voltage electric.
 18K Voltage electric insulation protection

Precaution and maintenance of the shoe: To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

1. Compression Resistance For Whole Footwear. ASTM F 2412-11, C/75.

	ASTM F2413 Requirement	Pass/Fail
Interior Height Clearance Left: 0.885 in	> 0.5 in	Pass
Right: 0.913 in	> 0.5 in	Pass

2. Puncture Resistance For Puncture Resistant Devices. ASTM F 2412-11, 11.

	ASTM F2413 Requirement	Pass/Fail
The test pin did not penetrate beyond the face of the material nearest the foot before 1200N.	Min. 1200N	Pass

3. Flex Resistance For Puncture Resistant Devices. ASTM F 24-11, 11.7.

	ASTM F2413 Requirement	Pass/Fail
--	------------------------	-----------

Left: No signs of de-lamination of layers or cracking after 1.5 million flexes	*	Pass
Right: No signs of de-lamination of layers or cracking after 1.5 million flexes	*	Pass

4. Impact Resistance For Whole Footwear. ASTM F 2412-11, I/75.

	ASTM F2413 Requirement	Pass/Fail
Interior Height Clearance Left: 0.570 in	> 0.5 in	Pass
Right: 0.629 in	> 0.5 in	Pass

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.